

# INDUSTRIAL

## SERIES: SSLVHT/G/BJG

BRACKET: STAINLESS STEEL  
 WHEEL: HIGH TEMPERATURE RESISTANT  
 WHEELS 220 °C, 260 °C OR 280 °C  
 BEARING: PLAIN / BALL BEARING

STAINLESS STEEL  
**INOX**



MEDIUM



SSLVHT/G	SWIVEL									KG
SS100LV4HT 220	100	38		105x85	80x60	9	40	128	150	150
SS100LV4HTG 280	100	38		105x85	80x60	9	40	128	200	200



SSLVHT/G	FIXED								KG
SS100LV8HT 220	100	38		105x85	80x60	9		128	150
SS100LV8HTG 280	100	38		105x85	80x60	9		128	200



SSLVHT/G	BOLT HOLE								KG
SS100LVBH12HT 220	100	38				12.1	40	128	150
SS100LVBH12HTG 280	100	38				12.1	40	128	200



SSLVHTBJG	SWIVEL								KG
SS80LV4HT 260	80	30		105x85	80x60	9	40	106	200
SS80LV4HTBJG 260	80	30		105x85	80x60	9	40	106	200
SS100LV4HT 260	100	32		105x85	80x60	9	40	128	220
SS100LV4HTBJG 260	100	32		105x85	80x60	9	40	128	220
SS125LV4HT 260	125	40		105x85	80x60	9	40	155	250
SS125LV4HTBJG 260	125	40		105x85	80x60	9	40	155	250



SSLVHTBJG	FIXED								KG
SS80LV8HT 260	80	30		105x85	80x60	9		106	200
SS80LV8HTBJG 260	80	30		105x85	80x60	9		106	200
SS100LV8HT 260	100	32		105x85	80x60	9		128	220
SS100LV8HTBJG 260	100	32		105x85	80x60	9		128	220
SS125LV8HT 260	125	40		105x85	80x60	9		155	250
SS125LV8HTBJG 260	125	40		105x85	80x60	9		155	250



SSLVHTBJG	BOLT HOLE								KG
SS80LVBH12HT 260	80	30				12.1	40	106	200
SS80LVBH12HTBJG 260	80	30				12.1	40	106	200
SS100LVBH12HT 260	100	32				12.1	40	128	220
SS100LVBH12HTBJG 260	100	32				12.1	40	128	220
SS125LVBH12HT 260	125	40				12.1	40	155	250
SS125LVBH12HTBJG 260	125	40				12.1	40	155	250

260°C CONSTANT (280°C SHORT PERIODS)(SSLVHTBJG ONLY)